

SOFT-ASSISTANT

CONTENTS

1. CHARACTERISTICS OF THE SOFT-ASSISTANT	3
1.1 Its functions	3
1.2 Minimum system requirements	3
1.3 Material supplied with the assistant	3
2. INSTALLATION INSTRUCTIONS	4
2.1 INSTALLATION	4
2.2 RUNNING.....	4
3. OPERATING	5
4. USER MANUAL	6
4.1 Application	6
4.2 Configuration.....	6
4.2.1 Application data.....	6
4.2.2 Configurable fields	6
4.2.3 Users	7
4.3 Language	8
4.4 Session.....	8
4.5 Assistant	8
4.5.1 Options and functions (driver).....	9
4.5.2 Devices	9
4.6 Work with installations.....	10
4.6.1 Creation of a new installation.....	11
4.6.1.1 <i>Structure</i>	11
4.6.1.2 <i>User groups</i>	13
4.6.1.3 <i>Universal codes</i>	14
4.6.2 Code registration / cancellation	15
4.6.2.1 <i>Registration</i>	15
4.6.2.2 <i>Cancellation</i>	17
4.6.3 Configuring / Editing user data	17
4.6.4 Save / Record installations	18
4.8 Replacements, reserves.....	19
4.8.1 Replacement	19
4.8.2 Allocating reserved position.....	19
4.9 Searches	19
4.10 Lists	19
4.10.1 Group details	19
4.10.2 Equipment memory	19
4.11 Copies	20
4.11.1 Save	20
4.11.2 Restore.....	20
5. Tutorial	21
5.1 Example of installation 1	21
5.2 Example of installation 2.....	21

1. CHARACTERISTICS OF THE SOFT-ASSISTANT

Soft-ASSISTANT is installation management software.

1.1 ITS FUNCTIONS

The functions that can be carried out using the Soft-ASSISTANT are as follows:

- Installation management
- Configuration of equipment from the MOTION range

1.2 MINIMUM SYSTEM REQUIREMENTS

- Pentium III
- Windows 2000, XP or superior
- 128 Mbytes of RAM
- 100 Mbytes of free hard drive
- CD-ROM drive
- Free USB port
- ASSISTANT

1.3 MATERIAL SUPPLIED WITH THE ASSISTANT

The ASSISTANT is made up of the following parts:

- CD-ROM containing the Soft-ASSISTANT management programme.
- USB cable to connect the ASSISTANT to the PC.
- Installation guide.
- ASSISTANT programming tool.

2. INSTALLATION INSTRUCTIONS

2.1 INSTALLATION

Insert the CD-ROM in the corresponding PC drive.

Connect the USB cable to the programmer and the PC. A window will open on the PC containing the message "New hardware found" and the Windows assistant for new hardware found will auto-run. Follow the instructions given on screen. During hardware installation, the assistant will ask you to select the USB driver path. Select the CD-ROM drive.

The Soft-ASSISTANT setup application will then start from the CD-ROM. Follow the instructions given on screen.

2.2 RUNNING

On running the application, the programme will request a login and password. The login is "softadmin" and the password is "assistant" by default.

3. OPERATING

The Assistant programmer is a tabletop tool for installation management.

The equipment can be connected to the PC using the USB cable supplied. The POWER light indicates the correct power supply to the equipment. The FUNCTION light indicates that the programmer is running. The area marked as PROGRAMMING AREA is where the operating devices must be located. The memory cards are inserted in the connector at the front of the equipment.

Connection status



The status button indicates the connection status. If it is red, this indicates that the programmer is not connected to the PC. If it is green, the connection is correct. By clicking on the status button the programme indicates whether the Assistant is correctly connected to the Soft-Assistant programme or not.

Connections

- USB connector
- Memory and event card connector
- BUS-L equipment connector

Programming of different devices (see Section 4.5 ASSISTANT in the 4.USER MANUAL)

- Transmitters
- Proximity elements
- Memory and event cards
- Receivers
- Access control stations
- Bus-L elements

4. USER MANUAL


4.1 APPLICATION

On running the application, a form will appear to enter the login and password.



4.2 CONFIGURATION

From the main menu bar, click on Application, Configuration and the application configuration window will appear.



This window can be used to update all the data related to general application and application user information. Three tabs will appear that correspond to the following configurable data.

4.2.1 Application data

This allows for the workstation data to be recorded.

4.2.2 Configurable fields

This allows for a series of fields to be configured, their format chosen and whether they are to be visible fields (those appearing in the search lists). Example: field name (Telephone) and type (Numerical).

Application data			
Application data Configure fields Users			
Field 1:	Visible <input checked="" type="checkbox"/>	Description: Telephone	Type: Numerical
Field 2:	Visible <input checked="" type="checkbox"/>	Description: Delivery date	Type: Text
Field 3:	Visible <input type="checkbox"/>	Description:	Type:
Field 4:	Visible <input type="checkbox"/>	Description:	Type:
Field 5:	Visible <input type="checkbox"/>	Description:	Type:
Field 6:	Visible <input type="checkbox"/>	Description:	Type:
Field 7:	Visible <input type="checkbox"/>	Description:	Type:
Field 8:	Visible <input type="checkbox"/>	Description:	Type:
Field 9:	Visible <input type="checkbox"/>	Description:	Type:
Field 10:	Visible <input type="checkbox"/>	Description:	Type:

4.2.3 Users

This allows for several users with access to the application and with configurable permissions for each user.

The screenshot shows the 'Edit User' dialog box. On the left, there's a sidebar with fields for 'Name', 'Surname', and 'Group'. Below these are buttons for 'New', 'Search', and a magnifying glass icon. A list titled 'Users found:' shows one entry: 'softadmin' under 'Nombre' and 'assistant' under 'Apellidos'. On the right, the main panel has tabs for 'User data' and 'Permissions'. Under 'User data', fields include 'User' (john), 'Password' (*****), 'Name' (john), 'Surname' (smith), 'Address' (empty), 'City' (empty), 'Postcode' (empty), 'Country' (empty), 'E-Mail' (empty), 'Contact telephone' (empty), and a dropdown 'Group' set to 'Gestor: Usuario que gestiona los nuevos elementos'. At the bottom are buttons for 'Delete', 'Save', 'Cancel', and a red 'X'.

To enter a new user, click on the New button and all the fields to be completed will appear blank in the User Edit window. (Enter a login, a password and other personal details as required). Pre-established access levels can be selected or established manually using the Permissions tab. Permissions depend on the programme functions and the equipment to be handled.

If you want to search for a user, the search can be made by first name, surname or user group. A list will appear under the search containing all the users found according to that particular search. If the search fields are left blank, all users will appear on clicking on the Search button.

The screenshot shows the 'Edit User' dialog box with the 'Permissions' tab selected. The left side of the main area displays a hierarchical tree of permissions. The 'Servicios' node is expanded, showing 'Access to Soft-ASSISTANT', 'Universal codes', 'Programming Installations' (which is expanded to show 'Management'), 'Copies', 'Listings', 'Users' (expanded to show 'New', 'General', 'Own', 'Assistant', 'Searches'), 'Configuration' (expanded to show 'Configurable fields' and 'General Information'), and 'Installations' (expanded to show 'Channels assignation', 'Structure', and 'Groups of Users'). The 'Devices' node is also expanded, showing 'Controller', 'Programming device' (which is expanded to show 'ASSISTANT'), 'Receiver' (expanded to show 'BASE500-1', 'BASE500-2', 'STICK500', 'WAVE500-1', 'WAVE500-1B', 'WAVE500-2', and 'WAVE500-2B'), and 'Transmitter' (expanded to show 'GO-EVO2', 'GO-EVO4', 'GO-PRO2', and 'GO-PRO4'). Several checkboxes are checked, such as 'Access to Soft-ASSISTANT', 'Management' under Programming Installations, 'Management' under Configuration, and 'Structure' under Installations. The right side of the main area contains the same buttons as the previous screenshot: 'Delete', 'Save', 'Cancel', and a red 'X'.

To save the data, click on the Save button. You will then return to the main Configuration menu. To exit the window and return to the main menu, click on the Cancel button. The data will not be saved.

4.3 LANGUAGE

To change the application language, click on Application and Language on the menu bar and choose the required language. The initial window will appear where you must enter your login and password again. On entering, the language will have changed automatically.



4.4 SESSION

To begin a session, click on File, Close Session on the menu bar or Close Session on the tool bar. A form will appear to enter a new login and password.

In the event of you forgetting your login and/or password, contact the system administrator.
The start of a session conditions the possibilities of action for users according to the profile allocated.
A session must be started for the system to be initialised, although another session can be started at any time.




Exit: This menu option ends the application.

4.5 ASSISTANT

This allows for independent work with any device (e.g. add installer code). The Assistant programming tool must be connected for this.

To run this option, click on the Assistant button on the tool bar.

Select the device type and model, click on Load device and a window will appear on the right containing the options and functions available for the selected device.



4.5.1 Options and functions (driver)

- **Configuration:** this allows for the device configuration to be read, changed and saved to the device. The fields with a shaded value cannot be modified.
- **Memory:** This allows for the contents of a device's memory to be read, modified and saved to the device.
- **Events:** This allows for the contents of an events card in a device to be read and formatted.
- **Commands:** this shows a series of functions that can be carried out on the device (e.g. formatting a memory in the case of a receiver)

To modify any field, double click on the field to be modified with the left-hand button of the mouse. Any modification made will be indicated by a colour change on the line modified.

4.5.2 Devices

1) TRANSMITTERS

Configuration	
Name	Description
Device information	Non-editable device characteristics data
PIN configuration	Configuration of the PIN, the expired PIN and the relays with PIN to be allocated to each channel
Replacement	

Commands	
Command	Description
FORMAT	This eliminates the installer code from the device
SET INSTALL	This inserts the installer code in the device
SELECT	Reserved function

2) RECEIVERS

Configuration	
Name	Description
Device information	Non-editable device characteristics data
PIN configuration	Configuration of the PIN, the expired PIN and the relays with PIN to be allocated to each channel
Advanced configuration	Forbids radio / manual programming
Minimum device	Sets the minimum device to operate on the equipment

Commands	
Command	Description
FORMAT	Resets the memory card
SET INSTALL	This inserts the installer code in the card
PIN RADIO	Configures the PIN on the receiver by radio


3) PROGRAMMER

Configuration	
Name	Description
Boot version	This allows for the operative system version of the Assistant to be read
Firm version	This allows for the programme version of the Assistant to be read

Commands	
Command	Description
UPDATE	Updates the Assistant firmware

4.6 WORK WITH INSTALLATIONS

- **Open:** this opens the existing installation. At the main menu, click on Installation and Open and a list of all existing installations will open. This allows for an installation to be sought by name, address or person to contact.
- **New:** this creates a new installation
- **Close:** new installation
- **Delete:** this deletes an installation





On opening an installation, this icon will appear. If the installation has no installer code, the icon will be open and green. If the installation has an installer code, the icon will be closed and red.

4.6.1 Creation of a new installation

Creation of a new installation

Name of installation			
<input type="text" value="Commercial centre"/>			
Address			
<input type="text"/>			
City	Postcode	Country	
<input type="text"/>	<input type="text"/>	<input type="text"/>	
Contact		Contact telephone	
<input type="text"/>		<input type="text"/>	
<input type="checkbox"/> Work with installer code			
Save Close			

Complete the fields on the new installation creation form and click on Save. A window will appear with two tabs on the left: Structure and User Group.

To access the different options of the Structure Tree and the User Group Tree, click with the right-hand button of the mouse on the line of the tree to be operated and a pop-up menu will appear containing these options.

4.6.1.1 Structure

This shows an installation with all its associated devices.

Estructure **Users Groups**


Installation

Edit Installation:

Installation data

Name of the installation			
<input type="text" value="Shopping center"/>			
Address			
<input type="text"/>			
City	Postcode	Country	
<input type="text"/>	<input type="text"/>	<input type="text"/>	
Contact		Contact telephone	
<input type="text"/>		<input type="text"/>	
<input type="checkbox"/> Work with installer code			
Save Cancel			

- a) **Add equipment:** This allocates the equipment location and selects the model from the form.



- b) **Edit equipment:** A form with three tabs will appear: Relays (where the active relays can be configured), Configurable data (pin, relay timer, etc.) and Code table (memory position, code, relay/channel configuration and counter, etc.).

The screenshot shows a software window titled "Edit Device:" with a yellow header bar. Below it is a "Device location" field with "Main building" and a "Device model" field with "WAVE500-2B". The main area contains a tabbed panel with "Relays" selected. Under "Relays", there are four entries: "Relay 1: Rolling door" (checkbox checked), "Relay 2: Sectional door" (checkbox checked), "Relay 3: Pedestrian door" (checkbox checked), and "Relay 4: " (checkbox unchecked). Below the tabs are buttons for "Save in receiver" (with a disk icon), "Save in Database" (with a disk icon), "Cancel", and a close button with an "X". There are also tabs for "Configuration" and "Table of codes".

Once the installation with its equipment has been created, it will appear in the structure tree.



- c) **Delete equipment:** This allows for the equipment selected to be deleted.
- d) **Save equipment memory:** This saves the codes generated and configuration of the device modified by the programme to the equipment memory (this memory must be inserted in the Assistant programmer).
- e) **Export to Excel:** This allows for the contents of the memory to be exported for work in Excel.


4.6.1.2 User groups

The creation of user groups enables you to effectively manage access to different areas of the installation.

Each user group can access the previously selected area, each of the devices and relays for said devices being considered an area. Thus, the channel to operate in each relay can be selected.



- a) **Add group:** On adding a group, a form will appear on the right of the screen where a name must be allocated to the group and the configuration required for devices, relays and channels chosen.



- b) **Delete group:** This allows for the group selected to be deleted.
- c) **Group list:** A table will appear (code, type, group, name, contact, ID number, place, visible configurable fields)

To list all groups: choose the List ALL option from Group.


To list one group: choose the List group option from the selected group.

- d) **Configure group:** this allows for the selected group to be edited and its configuration changed.
- e) **Export to Excel:** This allows for the user list of a group to be exported to edit its data in Excel.
- f) **Import from Excel:** This allows for data on the users in a group be imported from an Excel file.

4.6.1.3 Universal codes


Universal codes are used by installation installers or maintenance staff. Thus, a single device may be associated to all the required installations.

Before registering a universal code, the programme must be entered manually.
On the menu bar, go to Code Management, Universal and then Management.



A form will appear containing the list of universal codes entered. To enter a new code, click on New. Select the device model from the form and enter its code using the keypad or click on the field with the right-hand button of the mouse to enter the code by radio. Complete the user information fields (optional although highly recommended).

On accepting, the programme lists the codes entered.



A universal code can be registered from the Group tree or from the Code Management, Universal, Registrations option from the menu bar. If the registration is made from the menu bar, no installation has to be open, although the installation to which the codes and group are to be registered must be selected.

Select the code to register. On accepting, the programme lists the codes registered.


4.6.2 Code registration / cancellation

4.6.2.1 Registration

This allows for codes to be registered manually or sequentially on an installation or for reserve codes to be generated.

Registrations can be made from the Group tree or from the Code Management, Registrations option from the menu bar.

From the User group tree



From the menu bar



a) Manual Registration

Select the device model to be registered and enter its code using the keypad or click on the field with the right-hand button of the mouse to enter the code by radio. Complete the user information fields (optional).

On accepting, the programme lists the codes registered.

b) Sequential Registration

Select the device model to be registered, enter the initial code and the amount of devices required or the end code using the keypad. To enter the code by radio, click on the button on the right of the field. Complete the user information fields (optional).

On accepting, the programme lists the codes registered.

c) Reserves

Select the device model to be registered and enter the amount of devices required. On accepting, the programme lists the codes registered.

d) Universal

A universal code can be registered from the Group tree or from the Code Management, Universal, Registrations option from the menu bar. If the registration is made from the menu bar, no installation has to be open, although the installation to which the codes and group are to be registered must be selected.

Select the code to register. On accepting, the programme lists the codes registered.


4.6.2.2 Cancellation

This allows for codes to be deleted individually or by group.


From the group list screen, click on the code or codes to be deleted using the right-hand button of the mouse and a pop-up menu will appear. Click on Delete.

4.6.3 Configuring / Editing user data


Click on any box in the row of the list to be edited with the right-hand button of the mouse. A pop-up menu will appear with several options available.



- a) **Edit:** this allows for a first name, surname, ID number and place number of the device user to be added or modified.



- b) **Field display:** this allows for the fields to be displayed in the group list to be selected. Select the fields and click on Save. The fields selected will appear to the right of the group list. Only the fields configured as visible will be displayed (see Section 4.2.2 Configurable Fields).



- c) **Copy / Cut:** this allows for one or several lines of the code list to be copied and pasted to another installation. It also allows for lines from the code list to be cut and pasted to another installation or another group.
- d) **Export to Excel / Import from Excel:** This allows for the user list of a group to be exported to edit its data in Excel or import it.

4.6.4 Save / Record installations

- a) **Save to database:** this saves all the installation in the programme database.
 b) **Save to device:** this saves the memory of each device individually by selecting it.

4.8 REPLACEMENTS, RESERVES

4.8.1 Replacement

Should a device be lost or stolen, it can be deleted and replaced through the programme.

Select the code to be replaced from the group list using the right-hand button of the mouse and click on Replacement. The programme waits for radio reception of the new code to be inserted into the database, which will be saved to the receiver/station when the user reaches the installation.

4.8.2 Allocating reserved position

To submit devices with reserve codes, select the reserve code from the group list using the right-hand button of the mouse and click on Save code. The programme waits for radio reception of the new code to be inserted into the database, which will be saved to the receiver/station when the user reaches the installation.

4.9 SEARCHES

This allows for searches to be made by surname, code, installation or other fields (visible configurable fields)

Search result								
Model	Code	Name	Surname	National Identity Card No.	Post	Installation	Group	
GO-PRO2	4345				0	Shopping center	offices	
GO-PRO2	4346				0	Shopping center	offices	
GO-PRO2	4347				0	Shopping center	offices	
GO-PRO2	4348				0	Shopping center	offices	
GO-PRO2	4349				0	Shopping center	offices	
GO-PRO2	4350				0	Shopping center	offices	
GO-PRO2	4351				0	Shopping center	offices	
GO-PRO2	4352				0	Shopping center	offices	
GO-PRO2	4353				0	Shopping center	offices	
GO-PRO2	4354				0	Shopping center	offices	
GO-PRO2	4355				0	Shopping center	offices	
GO-PRO2	4356				0	Shopping center	offices	
GO-PRO2	4357				0	Shopping center	offices	
GO-PRO2	4358				0	Shopping center	offices	
GO-PRO2	4359				0	Shopping center	offices	
GO-PRO2	4360				0	Shopping center	offices	
GO-PRO2	4361				0	Shopping center	offices	
GO-PRO2	4362				0	Shopping center	offices	
GO-PRO2	4363				0	Shopping center	offices	
GO-PRO2	4364				0	Shopping center	offices	
GO-PRO2	4365				0	Shopping center	offices	
GO-PRO2	4366				0	Shopping center	offices	
GO-PRO2	4367				0	Shopping center	offices	
GO-PRO2	4368				0	Shopping center	offices	
GO-PRO2	4369				0	Shopping center	offices	
GO-PRO2	4370				0	Shopping center	offices	
GO-PB02	4371				0	Shopping center	offices	

4.10 LISTS

4.10.1 Group details

A list of all the codes of a group or several groups. The installation must be open for it to be displayed.


4.10.2 Equipment memory

List of the configuration and codes for a receiver. Only the configuration, only the codes or everything at the same time can be displayed.

The lists will be displayed on the screen as a preliminary view before printing. They can be printed directly or

exported to different formats (rtf, pdf, html, xls, tif, text).

4.11 COPIES



4.11.1 Save

Copy of the database (to a file): Once an installation has been created, it is wise to make a back-up copy of the database.

4.11.2 Restore

Copy of the database (from a file): The restore procedure can be of great use in the event of accidental loss of the database. This procedure replaces the programme database. The modifications made after the last back-up copy will be lost.

5. TUTORIAL

5.1 EXAMPLE OF INSTALLATION 1

5.2 EXAMPLE OF INSTALLATION 2

E Programador ASSISTANT

Es una herramienta de sobremesa que permite gestionar instalaciones. Se suministra con un software para PC y un cable de comunicación USB.

CARACTERÍSTICAS TÉCNICAS

Frecuencia	868,35MHz
Alimentación	USB
Consumo	<100mA
Potencia radiada	<25mW
Temperatura func.	-20°C - +85°C
Estanqueidad	IP20
Dimensiones	150x120x45mm

FUNCIONES:

- Gestionar instalaciones
- Configurar equipos de la gama MOTION

REQUERIMIENTOS MÍNIMOS

- Pentium III
- Windows 2000
- 128Mbytes de memoria RAM
- 100Mbytes espacio libre en disco duro
- Unidad lectora de CD-ROM
- Un puerto USB

INSTALACIÓN

Insertar el CD-ROM en la unidad de PC correspondiente. Aparecerá una pantalla de ayuda a la instalación.

Conectar el cable USB al programador y al PC. Se abrirá una pantalla en el PC con el mensaje "Nuevo hardware encontrado" y se auto-ejecutará el asistente para hardware nuevo encontrado de Windows. Siga las instrucciones que le irán apareciendo en pantalla. Durante la instalación del hardware, el asistente le preguntará que seleccione la ruta del driver USB, debe seleccionar la unidad de CD-ROM.

Seguir las instrucciones de la ayuda para la instalación o actualización del software.

EJECUCIÓN

Al ejecutar la aplicación, el programa solicitará un nombre de usuario y una contraseña. Por defecto el nombre de usuario es "softadmin" y la contraseña "assistant".

USO DEL PROGRAMADOR

Para información véase la ayuda del programa Soft-ASSISTANT.

El fabricante se reserva el derecho a cambiar especificaciones de los equipos sin previo aviso.

DECLARACIÓN DE CONFORMIDAD CE

La empresa

JCM TECHNOLOGIES, S.A.

C/Bisbe Morgades, 46 Baixos

08500 VIC – Barcelona

SPAIN

declara que el producto que se menciona a continuación cumple con las disposiciones pertinentes de acuerdo a lo expuesto en el artículo 3 de la Directiva R&TE 1999/05/CE, siempre y cuando el uso sea conforme a lo previsto, habiendo sido sometido a la aplicación de las siguientes normas:

Producto: Programador 868,35MHz

Fabricado por: JCM TECHNOLOGIES, S.A.

Marca comercial: JCM

Tipo: ASSISTANT

Entorno de uso: Residencial, comercial e industria ligera

Normativas:

- Telecomunicaciones EN 300 220-1 v1.3.1 (2000-09), EN 300 220-3 v1.1.1 (2000-09)
- Compatibilidad electromagnética EN 301489-3 v1.3.1 (2001-11), EN 301489-1 v1.3.1 (2001-09)
- Baja Tensión EN 60730-1:2000

Vic a 01/02/05

JUAN CAPDEVILA MAS
Director General

F Programmateur ASSISTANT

Il s'agit d'un outil de bureau qui permet de gérer les installations. Il est livré avec un logiciel pour PC ainsi qu'un câble de communication USB.

DONNÉES TECHNIQUES

Fréquence	868,35MHz
Alimentation	USB
Consommation	<100mA
Puissance	<25mW
Température fonct.	-20°C - +85°C
Etanchéité	IP20
Dimensions	150x120x45mm

FONCTIONS :

- Gérer les installations
- Configurer les produits du gamma MOTION

MATÉRIEL MINIMUM

- Pentium III
- Windows 2000
- 128Mbytes de memoria RAM
- 100Mbytes espacio libre en disco duro
- Unidad lectora de CD-ROM
- Un puerto USB

INSTALLATION

Introduisez le Cd-rom dans le lecteur de PC correspondant. Un programme d'aide s'affichera à l'écran.

Reliez le câble USB au programmateur et au PC. Le message « Nouveau matériel détecté » s'affichera alors sur le PC, tandis que l'assistant de Windows destiné au nouveau matériel s'auto exécutera. Suivez les instructions qui s'afficheront à l'écran. Au cours de l'installation du matériel, lorsque l'assistant vous demandera d'indiquer le chemin du pilote USB, sélectionnez le lecteur de Cd-rom.

Suivez les instructions du programme d'aide pour l'installation ou actualisation du software.

EXÉCUTION

Lors de la première exécution de l'application, le programme vous demandera d'indiquer le nom d'utilisateur et le mot de passe. Par défaut le nom d'utilisateur est « softadmin » et le mot de passe est « assistant ».

EMPLOI DU PROGRAMMATEUR

Pour information, consultez l'aide du programme Soft-ASSISTANT.

Le fabricant se réserve le droit de modifier les caractéristiques du matériel sans préavis.

DÉCLARATION DE CONFORMITÉ CE

La société

JCM TECHNOLOGIES, S.A.

C/Bisbe Morgades, 46 Baixos

08500 VIC – Barcelona

SPAIN

déclare que le produit ci-après, lorsqu'il est utilisé en conformité, satisfait aux exigences fondamentales de l'article 3 de la Directive R&TE 1999/5/CE, et que les normes suivantes ont été appliquées:

Produit: Programmateur 868,35MHz

Fabriqué par: JCM TECHNOLOGIES, S.A.

Marque: JCM

Type: ASSISTANT

Domaines d'utilisation: Résidentiel, commercial et industrie légère

Normes:

- Télécommunications EN 300 220-1 v1.3.1 (2000-09), EN 300 220-3 v1.1.1 (2000-09)
- Compatibilité électromagnétique EN 301 489-3 v1.3.1 (2001-11), EN 301 489-1 v1.3.1 (2001-09)
- Basse tension EN 60730-1 (2000)

Vic, le 01/02/05

JUAN CAPDEVILA MAS
Directeur Général

GB ASSISTANT programmer

This is a tabletop, installer code management tool. It is supplied with software for PCs and a USB communications cable.

TECHNICAL DATA

Frequency	868,35MHz
Power supply	USB
Consumo	< 100mA
Potencia	< 25mW
Radiated power	< 25mW
Working temperature	-20°C - +85°C
Watertightness	IP20
Dimensions	150x120x45mm

FUNCTIONS:

- Installations management
- Configure products of the MOTION gamma

MINIMUM REQUIREMENTS

- Pentium III
- Windows 2000
- 128Mbytes RAM memory
- 100Mbytes free space on hard drive
- CD-ROM read unit
- USB port

INSTALLATION

Insert the CD-ROM in the corresponding PC unit. A help for the installation will appear on the screen.

Connect the USB cable to the programmer and the PC. A screen will open on the PC with the message "Found new Hardware" and the Windows assistant for new hardware found will auto run. Follow the instructions that appear on the screen. During hardware installation, the assistant will ask you to select the USB driver route. You should select the CD-ROM unit.

Follow the instructions of the help for the software installation or actualisation.

EXECUTION

When executing the programme for the first time, the program will ask you to enter the user's name and the password. By default the user's name is "softadmin" and the password is "assistant".

USE OF THE PROGRAMMER

For information, please read the help in the Soft-ASSISTANT programme.

The manufacturer reserves the right to modify equipment specifications without prior notice.

EC DECLARATION OF CONFORMITY

The manufacturer

JCM TECHNOLOGIES, S.A.

C/Bisbe Morgades, 46 Baixos

08500 VIC – Barcelona

SPAIN

declares herewith that the product designated below complies with the relevant fundamental requirements as per Article 3 of the R&TE Directive 1999/5/CE, and that the following standards apply:

Product: Programmer 868,35MHz

Manufactured by: JCM TECHNOLOGIES, S.A.

Trade mark: JCM

Type: ASSISTANT

Environment of use: Residential, commercial and light industry

Standards:

- Telecommunication EN 300 220-1 v1.3.1 (2000-09), EN 300 220-3 v1.1.1 (2000-09)
- Electromagnetic Compatibility EN 301 489-3 v1.3.1 (2001-11), EN 301 489-1 v1.3.1 (2001-09)
- Low Voltage EN 60730-1 (2000)

Vic, 01/02/05

JUAN CAPDEVILA MAS
General manager

I Programmatore ASSISTANT

Si tratta di un utensile da tavolo che consente di gestire installazioni. Viene fornito con un software per PC e un cavo di comunicazione USB.

DATI TECNICI

Frequenza	868,35MHz
Alimentazione	USB
Consumo	< 100mA
Potenza	< 25mW
Temperatura funz.	-20°C - +85°C
Tenuta stagna	IP20
Dimensioni	150x120x45mm

FUNZIONI:

- Gestire installazioni
- Configurare apparecchi della gamma MOTION

CARATTERISTICHE MINIME

- Pentium III
- Windows 2000
- 128 Mb di memoria RAM
- 100 Mb di spazio libero su hard disc
- Unità lettore di CD-ROM
- Una porta USB

INSTALLAZIONE

Inserire il CD-ROM nella corrispondente unità del PC. Si eseguirà il programma di aiuto all'installazione. Connettere il cavo USB al programmatore e al PC. Si aprirà una schermata nel PC con il messaggio "Trovato nuovo hardware" e si eseguirà in forma automatica l'assistente per nuovo hardware di Windows. Seguire le istruzioni che appariranno sullo schermo. Durante l'installazione del hardware, l'assistente chiederà di selezionare l'indirizzo del driver USB, quindi si deve selezionare l'unità di CD-ROM. Seguire le istruzioni del programma di aiuto all'installazione o attualizzazione del software.

ESECUZIONE

Quando si esegue l'applicazione per la prima volta, il programma chiederà il nome dell'utente e la password. Per default, il nome dell'utente è "softadmin" e la password è "assistant".

USO DEL PROGRAMMATORE

Per informazioni, vedi la sezione d'aiuto del programma Soft-ASSISTANT. Il fabbricante si riserva il diritto di modificare le caratteristiche degli apparecchi senza previo avviso.

DICHIAZIONE DI CONFORMITÀ CEE

La empresa

JCM TECHNOLOGIES, S.A.

C/Bisbe Morgades, 46 Baixos

08500 VIC – Barcelona

SPAIN

dichiara che il prodotto di seguito descritto, nella destinazione olio prevista, è conforme ai requisiti fondamentali di cui all'articolo 3 della Direttiva R&TE 1999/5/CE, e che sono state applicate le seguenti norme:

Prodotto: Programmatore 868,35MHz

Prodotto da: JCM TECHNOLOGIES, S.A.

Marchio: JCM

Tipo: BASE15-1, BASE15-2, STICK15

Ambiente di uso: residenziale, commerciale e industria leggera

Norme:

- Telecommunicazione EN 300 220-1 v1.3.1 (2000-09), EN 300 220-3 v1.1.1 (2000-09)
- Compatibilità elettromagnetica EN 301 489-3 v1.3.1 (2001-11), EN 301 489-1 v1.3.1 (2001-09)
- Basse tension EN 60730-1 (2000)

Vic, 01/02/05

JUAN CAPDEVILA MAS
Amministratore delegato