

NOIRE

REMOTE CONTROLS AND RECEIVERS

NOIRE remote control are flexible; they can work at with fix code 433.92 MHz or with Rolling Code, to grant maximum safety. All NOIRE transmitters can be personalized though a *family code*, by using programming unit PRG NOIRE. The refined design, sober and essential, assures the maximum ergonomic comfort.

The remote control range is completed by code self-learning receivers and programmable outputs.

NOIRE TRANSMITTERS

NOIRE 2E e NOIRE 4E

NOIRE 2E and NOIRE 4E Portable transmitters 2/4 channels.

NOIRE 20

NOIRE 20 Multichannel transmitter to control up to 20 automations.

NOIRE TAXI

NOIRE TAXI 5 channels transmitter specially designed to be installed in the car. Automatically repeats the radio signal improving convenience and safety for the driver.



NOIRE 2E



NOIRE 4E



NOIRE 20



NOIRE TAXI

CHARACTERISTICS	NOIRE 2E	NOIRE 4E	NOIRE 20	NOIRE TAXI
Power supply/battery type	3 V / CR2032	3 V / CR2032	3 V / CR2430	3 V / CR2430
Absorbed current in transmitting	8 mA	8 mA	50 mA	50 mA
Transmitting frequency	433,92 MHz	433,92 MHz	433,92 MHz	433,92 MHz
Radiated power	150 µW	150 µW	900 µW	900 µW
Number of combinations	1048576	1048576	1048576	1048576
Number of functions	2	4	21	5
Working temperature	-20 +55 °C	-20 +55 °C	-20 +55 °C	-20 +55 °C

ACCESSORIES

SOFT NOIRE

Advanced software for archives management.



B3V2032

Lithium battery 3V CR 2032. Pack of 50 pcs.



MEM16

675 codes memory.



PTE

Transmitter-holder.



NOIRE RECEIVERS

NOIRE OC2

Noire OC2 plug in receiver for Telcoma control units. 2 channels.



NOIRE OC2

NOIRE RB2

NOIRE RB2 compact size universal receiver 12/24 Vac/dc power supply. 2 channels.



NOIRE RB2

NOIRE R4P

NOIRE R4P external universal receiver 4 channels. 12/24 V ac/dc power supply IP44.



NOIRE R4P

NOIRE 230 R4

NOIRE 230 R4 external universal receiver 4 channels. 230 V power supply. IP56.



NOIRE 230 R4

CHARACTERISTICS	NOIRE OC2	NOIRE RB2	NOIRE R4P	NOIRE 230 R4
Power supply	5 Vdc	12/24 Vac/dc	12/24 Vac/dc	230 V
Consumption in Stand-by	12 mA	40 mA	40 mA	12 mA
Relay contact max capacity	-	0,5 A	4 A	5 A
Relay contact max voltage	-	30 Vdc	30 Vdc	230 V
Number of outputs	2	2	4	4
Storage codes	163	163	163	163
Storage codes with MEM16	675	675	675	675
Protection level	-	-	IP 44	IP 56
Working temperature	-20 +55 °C	-20 +55 °C	-20 +55 °C	-20 +55 °C

ACCESSORIES

PRG NOIRE

Programming unit for adding/erasing transmitter codes and managing families of codes. Complete with power supply.



DAMA430

Antenna for 433 MHz receivers, complete with stainless steel bracket and connection cable (3 m).

